

TekCel D1000 Ultrasonic Option



TranTek Systems pre-engineered automation cells are cost-effective and offer the following features and benefits:


- Common bases for ease of installation and start-up
- Work cell design is adaptable to multiple configurations and applications
- Available with tooling for a turn-key single source solution
- Pre-engineered for shorter lead-times
- Low investment cost
- PLC/HMI and other features of high technical content are included
- Safety PLC is standard
- Customer selectable component options in base price
- Compatible with all robot manufacturers
- Easy tool accessibility from rear entry doors
- Obstruction-free cell access with hidden cable routing
- Preconfigured PLC/HMI base programs for easy start-ups



TRANTEK SYSTEMS 417 HUGHES DRIVE TRAVERSE CITY, MI 49696 PHONE: 231-946-6270 FAX: 231-946-3206 E-MAIL: INFO@TRANTEKSYSTEMS.COM TRANTEKSYSTEMS.COM

Standard Specifications

D1000 Ultrasonic Option



CAPACITIES

Max Weight Total	1300 pounds (590 kg)
Max Weight Per Side	500 pounds (227 kg)
Index Time 180°	2 seconds


WORK CELL DIMENSIONS

"A" - Dial Diameter	72" (1829mm)
"B" - Front Opening Width	81.75" (2076.7mm)
"C" - Overall Width	93.00" (2362mm)
"D" - Overall Length	176.19" (4475.2mm)
"E" - Dial Height	30.55" (775.9mm)
"F" - Opening Height	29.45" (748.1mm)
"G" - Overall Height	90.08" (2288.0mm)

OPTIONAL FEATURES

Remote Access	For off-site support
Weld Package(S)	Torch, reamer, power source, wire feeder & misc.
Light Hood	For vision applications

TRANTEK SYSTEMS 417 HUGHES DRIVE TRAVERSE CITY, MI 49696 PHONE: 231-946-6270 FAX: 231-946-3206 E-MAIL: INFO@TRANTEKYSTEMS.COM TRANTEKSYSTEMS.COM





INCLUDED FEATURES		
Dial Indexer with Plate	Robot 7th axis controlled indexer	
Light Curtains	25mm resolution cascadable	
Cell Lighting	Industrial led light bars	
Robot Riser	300 & 620mm height	
Two Safety Gates	Solenoid locking with internal release with lock-out	
Integrated Cell	Functionally programmed cell ready for tooling	
Stack Light	3 color red, amber & green	
Operator Runbar	Cycle start OPTO-Touch & E-Stop	
PLC (Choice Of)	AB CompactLogix Safety Processor 5069 L310ERS2 Siemens SIMATIC S7-1500 F	
HMI (Choice Of)	AB PanelView Plus 7-10" Siemens TP1200 Comfort Panel	
Paint Color (Choice Of)	Any RAL color pallet Industrial enamel	
Panel Color	Red, blue or charcoal 1/4" polymer	
Viewable Windows	1/4" clear polycarbonate panels	
PLC Main Panel	Low voltage control panel (24vdc)	
Power Distribution Panel	High voltage control panel (120vac-480vac)	
Quick Disconnect Tooling Features	Ethernet i/o available at tooling	
FRL & Drip Leg	1/2" drip leg, filter regulator & lock-out	